

VIDEX®

VIDEX IP65 SLE18 50W 5000Lm 5000K 230V

INDEX: VL-SLE18-0505

TECHNICAL CARD



LED Street Light




Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®

VIDEX IP65 SLE18 50W 5000Lm 5000K 230V

INDEX: VL-SLE18-0505



WARRANTY 2 YEARS

NEUTRAL WHITE



5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source or containing product Light source

Control gear replaceable -

Light source replaceable by the producer

Type of light source

Energy class of the light source F

Dimmable no

Directional (DLS) or non-directional (NDLS) light source DLS

Connected light source (cls) no

Color-tunable light source no

High luminance light source No

Mains (MLS) or non-mains (NMLS) light source	MLS
Anti-glare shield	No
Technology	LED

Electrical parameters

On-mode power (Pon) 50 W

Rated voltage, frequency AC 180-265 V, 50/60 Hz

Cable length 30 cm

Rated current 250 mA

Input interface Free wire ends

Electric shock protection class I

Displacement factor (cos φ1) 0.9

Survival factor 0.9

Energy consumption in on-mode of the light source (kWh/1000h) 50

Photometric parameters

Luminous flux 5000 Lm

Useful luminous flux (Φuse) 4500 Lm

Correlated color temperature 5000K (neutral white)

Peak luminous intensity 2160 cd

Beam angle 90 × 130°

Color rendering index (CRI) Ra > 80

On/Off cycles 20000

Lifetime (L70B50) 30000 h

INDEX: VL-SLE18-0505

Useful luminous flux of the light source reference	in a wide cone (120°)
Chromaticity coordinates (x)	0.34
Chromaticity coordinates (y)	0.359
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	outdoor use
Colour consistency in MacAdam ellipses (SDCM)	<6 (5000K)
CRI Min	Ra 80
CRI Max	Ra 88

Additional information

Vertical adjustment range	25°
Place of installation	Pillar, Wall
Place of application	outdoor
Impact protection	IK07
Housing colour	Black
Diffuser material	Polycarbonate (PC)
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Operating temperature range	-30° +50°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Aluminum alloy

Dimensions

EAN	4820246486019
In the package	1 pc.
Height	507 mm
Outer box	10 pcs.
Width	108 mm
Depth	76 mm
Unit nett weight	770g

Signs marking goods
Packaging marking

Recycling of waste, CE, Utilization



VIDEX[®]


VIDEX IP65 SLE18 50W 5000Lm 5000K 230V

INDEX: VL-SLE18-0505

VIDEX®

















VIDEX IP65 SLE18 50W 5000Lm 5000K 230V

INDEX: VL-SLE18-0505



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

-  The product must be used outdoors
-  Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network
-  Minimum distance from the illuminated object
-  The product can be installed and used in/on normally flammable surfaces
-  Waste recycling after the end of the product's service life
-  The product meets the requirements of EU directives
-  It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste
-  — Effective light beam angle
50°-130°
-  — Ra > 80 - color rendering index
Ra > 80
-  — Rated On/off cycles
20 000
-  — The product withstands a medium impact (e.g., from a blunt object)
IK07
-  — Nominal lifetime (hours)
30 000 h
-  — The product does not emit ultraviolet light
Free
-  — The product is incompatible with light regulators
Not Dimmable
-  — Operating temperatures range
-30°+50°C
-  — The flickering of the light does not exceed the permissible level
No Flicker
- — Colour consistency in MacAdam ellipses (SDCM)
CC1 5000K
- — The product does not contain mercury
Free
- — Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions
IP65

Date: 4.06.2026