



INDEX: VL-SLE18-1005

# **TECHNICAL CARD**





**LED Street Light** 

















### VIDEX IP65 SLE18 100W 10000Lm 5000K 220V

#### INDEX: VL-SLE18-1005



90×130°



Ra ≥ 80









30 000 h















IP65

#### **WARRANTY 2 YEARS**



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

#### **General parameters**

Light source or containing product	Light source
Control gear replaceable	-
Light source replaceable	by the producer

### Type of light source

source

Energy class of the light source	F
Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	DLS
Connected light source (cls)	no
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light	MIS

MLS

High luminance light source	No
Anti-glare shield	No
Technology	LED

### **Electrical parameters**

On-mode power (Pon)	100 W
Rated voltage, frequency	AC 180-265 V, 50/60 Hz
Cable length	30 cm
Rated current	500 mA
Input interface	Free wire ends
Electric shock protection class	I
Displacement factor (cos φ1)	0.9
Survival factor	0.9
Energy consumption in on-mode of the light source (kWh/1000h)	100

#### **Photometric parameters**

Luminous flux	10000 Lm
Useful luminous flux (Фuse)	9000 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	4100 cd
Beam angle	90 × 130°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h



# VIDEX IP65 SLE18 100W 10000Lm 5000K 220V

INDEX: VL-SLE18-1005

Useful luminous flux of the light source reference	in a wide cone (120°)
Chromaticity coordinates (x)	0.34
Chromaticity coordinates (y)	0.359
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	outdoor use
Colour consistency in MacAdam ellipses (SDCM)	<6 (5000K)
CRI Min	Ra 80
CRI Max	Ra 88

#### **Additional information**

Vertical adjustment range	25°
Place of installation	Pillar, Wall
Place of application	outdoor
Impact protection	IK07
Housing colour	Black
Diffuser material	Polycarbonate (PC)
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Operating temperature range	-30° +50°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Aluminum alloy

#### **Dimensions**

EAN	4820246486026
In the package	1 pc.
Height	597 mm
Outer box	10 pcs.
Width	108 mm
Depth	76 mm
Unit nett weight	950g

# Signs marking goods

Packaging marking Recycling of waste, CE, Utilization







INDEX: VL-SLE18-1005














We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

# VIDEX IP65 SLE18 100W 10000Lm 5000K 220V

#### INDEX: VL-SLE18-1005



The product must be used outdoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply



Minimum distance from the illuminated object



The product can be installed and used in/on normally flammable surfaces



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Effective light beam angle



Ra > 80 - color rendering index





Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The flickering of the light does not exceed the permissible level



Colour consistency in MacAdam ellipses (SDCM)



The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions

Date: 18.11.2025