

INDEX: VLE-T8-24154

TECHNICAL CARD





LED T8 Glass Tube













VIDEX-T8-LED-150-24W-NW

INDEX: VLE-T8-24154









330° Ra ≥ 80









-20° +40°C

CCT 4000K

WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Light source or containing product Light source

Type of light source

Energy class of the light source	Е
Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	24 W
Rated voltage, frequency	AC 185-265 V, 50/60 Hz
Rated current	208 mA
Energy consumption in on-mode of the light source (kWh/1000h)	24

Photometric parameters

Useful luminous flux (Φuse)	2700 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	330°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Colour consistency in MacAdam ellipses (SDCM)	<6 (4000K)
CRI Min	Ra 80
CRI Max	Ra 88

Additional information

Place of application	indoor
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20

Dimensions

EAN	5904405540701
In the package	1 pc.
Height	25 mm
Outer box	30 pcs.
Width	25 mm
Depth	1510 mm



VIDEX-T8-LED-150-24W-NW

INDEX: VLE-T8-24154


Signs marking goods

Packaging marking

Recycling of waste, CE, Not suitable for use under moisture, Utilization







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



Not suitable for use under moisture



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



— Ra > 80 - color rendering index



— Rated On/off cycles



— Nominal lifetime (hours)



The product is incompatible with light regulators



Operating temperatures range



Colour consistency in MacAdam ellipses (SDCM)



The product does not contain mercury



Class of protection against dust and moisture.

Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025