

VIDEX®

VIDEX-TOR-30W-BLACK

INDEX: VLE-TR04-304B

TECHNICAL CARD




LED Track Light



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

INDEX: VLE-TR04-304B



WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

| | |
|--|--------------------|
| Light source or containing product | Containing product |
| Light source replaceable | by the producer |
| Type of light source | |
| Dimmable | no |
| Directional (DLS) or non-directional (NDLS) light source | DLS |
| Color-tunable light source | no |
| Mains (MLS) or non-mains (NMLS) light source | MLS |
| Technology | LED |
| Energy efficiency class of the contained light source | F |

Electrical parameters

| | |
|---|------------------------|
| On-mode power (Pon) | 30 W |
| Rated voltage, frequency | AC 220-240 V, 50/60 Hz |
| Rated current | 145 mA |
| Input interface | 2 Wires Busbar |
| Electric shock protection class | II |
| Energy consumption in on-mode of the light source (kWh/1000h) | 30 |
| Displacement factor (cos φ1) | 0.9 |

Photometric parameters

| | |
|---|--------------------------|
| Useful luminous flux of the contained light source (Φuse) | 2400 Lm |
| Correlated color temperature | 4000K (neutral white) |
| Beam angle | 36° |
| Color rendering index (CRI) | Ra > 90 |
| Lifetime | 30000 h |
| On/Off cycles | 20000 |
| Useful luminous flux of the light source reference | in a narrow cone (90°) |
| Chromaticity coordinates (x) | 0.38 |
| Chromaticity coordinates (y) | 0.38 |
| R9 colour rendering index value | >0 |
| Colour consistency in MacAdam ellipses (SDCM) | <6 (4000K) |
| Flicker metric (Pst LM) | ≤1 |
| Stroboscopic effect metric (SVM) | ≤0.4 |

| | |
|---------|-------|
| CRI Min | Ra 90 |
| CRI Max | Ra 95 |

Additional information

| | |
|--|------------------|
| Place of installation | Busbar track |
| Place of application | indoor |
| Housing colour | Black |
| Minimum distance from the illuminated object | 0.5 m |
| Diffuser material | PMMA |
| Ultraviolet radiation | no |
| Operating temperature range | -20° +40°C |
| Suitable for installation in normally flammable surfaces | yes |
| Mercury content | Does not contain |
| Ingress protection | IP20 |
| Housing material | Aluminum alloy |

Dimensions

| | |
|----------------|---------------|
| EAN | 5904405541470 |
| Height | 180 mm |
| Width | 77 mm |
| Depth | 77 mm |
| In the package | 1 pc. |
| Outer box | 20 pcs. |

Signs marking goods

Packaging marking

Recycling of waste, CE, Utilization



VIDEX[®]**VIDEX-TOR-30W-BLACK****INDEX: VLE-TR04-304B**

INDEX: VLE-TR04-304B

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

