

INDEX: VLF-AK012

TECHNICAL CARD



Mini LED Flashlight



VIDEX VLF-AK012 400Lm 5000K

INDEX: VLF-AK012











ree	IPA
-	

RESISTANT	Not [

WARRANTY 2 YEARS

General parameters

Operation mode	HIGH, MIDDLE, LOW, RED ON, UV
Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

Photometric parameters

Useful luminous flux of the contained light source (Φ use)	400 Lm
Correlated color temperature	5000K (neutral white), Red, UV
Peak luminous intensity	4650 cd

Additional information

Housing colour	Gray

Fall protection	2 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery capacity	250 mAh
Battery type	Li-pol
Battery indicator	4 level
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Aluminum

Dimensions

EAN	4820246488129
In the package	1 pc.
Outer box	80 pcs.
Height	64 mm
Width	17 mm
Depth	17 mm
Unit nett weight	

Signs marking goods

Packaging marking	CE, Utilization





INDEX: VLF-AK012













INDEX: VLF-AK012











VIDEX VLF-AK012 400Lm 5000K

INDEX: VLF-AK012




VIDEX





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste

The protection is effective in case of a fall from a height of up to 2 meters

— The product is incompatible with light regulators

Operating temperatures range

The product does not contain mercury

Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 18.11.2025