

TECHNICAL CARD



Mini LED Flashlight

VIDEX®



WARRANTY 2 YEARS

General parameters

Operation mode	HIGH, MIDDLE, LOW, RED ON, UV
Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

Input interface	USB-C
-----------------	-------

Photometric parameters

Useful luminous flux of the contained light source (Φ_{use})	400 Lm
Correlated color temperature	5000K (neutral white), Red, UV
Peak luminous intensity	4650 cd

Additional information

Housing colour	Gray
----------------	------

VIDEX VLF-AK012 400Lm 5000K

INDEX: VLF-AK012

Fall protection	2 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery type	Li-pol
Battery capacity	250 mAh
Battery indicator	4 level
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Aluminum

Dimensions

EAN	4820246488129
In the package	1 pc.
Height	64 mm
Outer box	80 pcs.
Width	17 mm
Depth	17 mm
Unit nett weight	15g

Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------

VIDEX[®]

VIDEX VLF-AK012 400Lm 5000K

INDEX: VLF-AK012

VIDEX®

VIDEX VLF-AK012 400Lm 5000K

INDEX: VLF-AK012



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



Not Dimmable

— The product is incompatible with light regulators



— Operating temperatures range



Free

— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 24.06.2026