

VIDEX VL-SPC12B 1200W

INDEX: VL-SPC12B

TECHNICAL CARD



PIR motion and light sensor











VIDEX VL-SPC12B 1200W

INDEX: VL-SPC12B







Housing material

ABS, PE (Polyethylene)

WARRANTY 2 YEARS

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Free wire ends
Electric shock protection class	II
Standby Power (Psb)	<0.9 W

Photometric parameters

Sensor light threshold	10-2000 Lx
_	

Additional information

Place of installation	Ceiling, Flat surface, Wall
Place of application	indoor
Housing colour	Black
Ultraviolet radiation	no
Motion sensor	yes
Sensor type	PIR
Sensor time delay	10 s - 7 min
Sensor detection angle	360°
Sensor detection distance	2 - 8 m
Operating temperature range	-20° +40°C
Ingress protection	IP20

Dimensions

EAN	4820246484626
In the package	1 pc.
Height	88 mm
Outer box	50 pcs.
Width	88 mm
Depth	34 mm
Unit nett weight	88g

Signs marking goods

Packaging marking

Recycling of waste, CE, Utilization






VIDEX VL-SPC12B 1200W

INDEX: VL-SPC12B







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The product does not emit ultraviolet light



Operating temperatures range



Class of protection against dust and moisture.

Protection against solid objects larger than 12 mm; no protection against moisture

Date: 26.11.2025