

VIDEX[®]

VIDEX VLF-M048 1500Lm 5000k

INDEX: VLF-M048

TECHNICAL CARD



MULTIFUNCTIONAL LED OUTDOOR LANTERN



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 2 YEARS

General parameters

Operation mode	RED ON, RED FLASH, GREEN ON, FLOOD, FLOOD+SPOT, SPOT ON
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	yes
Technology	LED

Electrical parameters

On-mode power (P _{on})	10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φ _{use})	1500 Lm
Peak luminous intensity	4200 cd
Correlated color temperature	5000K (neutral white), 2700-6500K, Red, Green

VIDEX VLF-M048 1500Lm 5000k

INDEX: VLF-M048

Additional information

Housing colour	Black
Fall protection	2 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery type	Li-ion 18650 (2pcs)
Battery capacity	2200 mAh (2pcs)
Battery indicator	5 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Polyamide

Dimensions

EAN	4820246488150
In the package	1 pc.
Height	102 mm
Outer box	20 pcs.
Width	92 mm
Depth	40 mm
Unit nett weight	289g

Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------

INDEX: VLF-M048



VIDEX®

VIDEX VLF-M048 1500Lm 5000k

INDEX: VLF-M048



VIDEX[®]

VIDEX VLF-M048 1500Lm 5000k

INDEX: VLF-M048

VIDEX®

VIDEX VLF-M048 1500Lm 5000k

INDEX: VLF-M048

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



Dimmable

— The product supports brightness adjustment



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP66

— Class of protection against dust and moisture. The product has full protection against dust and powerful water jets