

TECHNICAL CARD



MULTIPURPOSE RECHARGEABLE LED FLASHLIGHT



WARRANTY 3 YEARS

General parameters

Operation mode	COB WHITE, COB RED, COB RED FLASH, COB UV, TOP
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	yes
Technology	LED

Electrical parameters

On-mode power (Pon)	5 W + COB 10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φuse)	400 Lm
Correlated color temperature	6500K (cold white), 4000K (neutral white)
Peak luminous intensity	900 cd

VIDEX VLF-M044UV

INDEX: VLF-M044UV

Additional information

Housing colour	Black, Orange
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 18650
Battery voltage	3.7 V
Battery capacity	2200 mAh
Battery indicator	5 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IPX2
Housing material	Polyamide, Thermoplastic rubber (TPR)

Dimensions

EAN	4820246483193
Height	150 mm
Depth	30 mm
In the package	1 pc.
Outer box	20 pcs.
Width	38 mm
Unit nett weight	117g

Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------

VIDEX[®]

VIDEX VLF-M044UV

INDEX: VLF-M044UV



VIDEX[®]**VIDEX VLF-M044UV****INDEX: VLF-M044UV**

VIDEX[®]

VIDEX VLF-M044UV


INDEX: VLF-M044UV



VIDEX®

VIDEX VLF-M044UV

INDEX: VLF-M044UV



VIDEX®

VIDEX VLF-M044UV

INDEX: VLF-M044UV



VIDEX®

VIDEX VLF-M044UV

INDEX: VLF-M044UV

VIDEX®

 MODEL | **MO44UV**

REPLACEABLE BATTERIES



Replace a discharged battery without interrupting the workflow.

VIDEX®

 MODEL | **MO44UV**

USB-C



Charge the battery directly in the flashlight.


VIDEX®

 MODEL | **MO44UV**

CHARGING INDICATOR



- - ≤ 100% charge
- - ≤ 80% charge
- - ≤ 60% charge
- - ≤ 40% charge
- - ≤ 20% charge
- - battery discharged

Displays current battery level while charging or discharging. With the light switched off, press and hold the button to see the battery status.

VIDEX®

 MODEL | **MO44UV**

LIGHTING MODES


 WITH BATTERY
2200mAh

	TOP	COB WHITE	COB RED ON	COB RED FLASH	COB UV
OUTPUT	200 Lm	400 Lm	5 Lm	5 Lm	/
RUNTIME	5h	2h 30min	37h	39h	4h
DISTANCE	60m	30m	5m	5m	/
INTENSITY	900cd	240cd	11cd	11cd	/

The above output parameters tested with the stock battery Videx 18650 2200mAh and may vary due to environmental conditions and actual batteries used.

VIDEX®

VIDEX VLF-M044UV

INDEX: VLF-M044UV



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



— The product supports brightness adjustment



— Operating temperatures range



— The product does not contain mercury