

INDEX: VL-SPF08R-W

TECHNICAL CARD







Recessed spotlight luminaire VL-SPF08R-W

INDEX: VL-SPF08R-W

X	°C	ŀ∕g	
IK07	-25° +50°C	Free	

IP20

WARRANTY 2 YEARS

Depth	92 mm
Outer box	50 pcs.
Width	92 mm

General parameters

Light source replaceable	end user
Electrical parameters	
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Free wire ends



Additional information

Place of installation	Ceiling, Recessed
Place of application	indoor
Impact protection	IK07
Housing colour	White
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

Dimensions

950










INDEX: VL-SPF08R-W





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

\bigcirc	Th	e product must be used indoors
К07	—	The product withstands a medium impact (e.g., from a blunt object)
"C -25" +50"C	—	Operating temperatures range
Free	—	The product does not contain mercury
IP20	_	Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture