



**INDEX: VL-SPF27R-B** 

# **TECHNICAL CARD**



Recessed spotlight luminaire











## VIDEX for GX53 lamp VL-SPF27R-B

#### **INDEX: VL-SPF27R-B**









#### **WARRANTY 2 YEARS**

General para	ameters
--------------	---------

**Light source replaceable** end user

## **Electrical parameters**

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	II

#### **Additional information**

Place of installation	Ceiling, Recessed
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

#### **Dimensions**

85906

In the package	1 pc.
Height	30 mm
Outer box	50 pcs.
Width	108 mm
Depth	108 mm
Unit nett weight	200g

## Signs marking goods

Packaging marking CE, Utilization






## VIDEX for GX53 lamp VL-SPF27R-B

**INDEX: VL-SPF27R-B** 







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025