

TECHNICAL CARD



Tactical LED Flashlight

VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG



WARRANTY 3 YEARS

General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, MOON, STROBE, RED HIGH, RED MIDDLE, RED LOW, GREEN HIGH, GREEN MIDDLE, GREEN LOW
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	20 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φ_{use})	2000 Lm
Peak luminous intensity	77600 cd

Correlated color temperature	5000K (neutral white), Red, Green
-------------------------------------	-----------------------------------

Additional information

Housing colour	Black
Fall protection	2 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery type	Li-ion 21700, Li-ion 18650
Battery capacity	4000 mAh
Battery indicator	5 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Heavy-anodized aircraft aluminum

Dimensions

EAN	4820246483704
In the package	1 pc.
Height	150 mm
Outer box	20 pcs.
Width	40 mm
Depth	31 mm
Unit nett weight	159g

VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG

Signs marking goods

Packaging marking

CE, Utilization



VIDEX[®]

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG

VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG



VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG



VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG

VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG



Color	State	Action	Result	Action	Result	
WHITE	OFF	Tap	ON	Release	OFF	
	OFF	Fully press	ON	Fully press	OFF	
	OFF	Press and hold	STROBE	Release	OFF	
	ON	Click	> TURBO > HIGH > MIDDLE > LOW > MOON >			
	ON	Press and hold for 0.5 sec.	STROBE	Click	Exit	
	RED	OFF	Tap	ON	Release	OFF
		OFF	Fully press	ON	Fully press	OFF
		OFF	Press and hold	STROBE	Release	OFF
		ON	Click	> HIGH > MIDDLE > LOW >		
		ON	Press and hold for 0.5 sec.	STROBE	Click	Exit

Notes: The flashlight automatically memorizes the last selected lighting mode (excluding Strobe mode) and applies it next time when turned on. Battery indication is always on if the light is switched on.

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegra opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

INDEX: VLF-AT255RG



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture.
The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter