

TECHNICAL CARD



Tactical LED Flashlight

VIDEX®



WARRANTY 3 YEARS

General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, MOON, STROBE, RED HIGH, RED MIDDLE, RED LOW, GREEN HIGH, GREEN MIDDLE, GREEN LOW
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	20 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Φ_{use})	2000 Lm
Correlated color temperature	5000K (neutral white), Red, Green

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG

Peak luminous intensity	77600 cd
--------------------------------	----------

Additional information

Housing colour	Black
Fall protection	2 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery capacity	4000 mAh
Battery type	Li-ion 21700, Li-ion 18650
Battery indicator	5 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Heavy-anodized aircraft aluminum

Dimensions

EAN	4820246483704
In the package	1 pc.
Outer box	20 pcs.
Height	150 mm
Width	40 mm
Depth	31 mm
Unit nett weight	159g

Signs marking goods

Packaging marking	CE, Utilization
--------------------------	-----------------

VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG

VIDEX[®]

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG

VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG

VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG



VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG



VIDEX®

VIDEX VLF-AT255RG 2000Lm 5000K

INDEX: VLF-AT255RG



Mode	Initial State	Action A	Result	Action B	Result
WHITE	OFF	Tap	ON	Release	OFF
	OFF	Fully press	ON	Fully press	OFF
	OFF	Press and hold	STROBE	Release	OFF
	ON	Click	> TURBO > HIGH > MIDDLE > LOW > MOON >		
	ON	Press and hold for 0.5 sec	STROBE	Click	Exit
GREEN	OFF	Tap	ON	Release	OFF
	OFF	Fully press	ON	Fully press	OFF
	OFF	Press and hold	STROBE	Release	OFF
	ON	Click	> HIGH > MIDDLE > LOW >		
	ON	Press and hold for 0.5 sec	STROBE	Click	Exit
RED	OFF	Tap	ON	Release	OFF
	OFF	Fully press	ON	Fully press	OFF
	OFF	Press and hold	STROBE	Release	OFF
	ON	Click	> HIGH > MIDDLE > LOW >		
	ON	Press and hold for 0.5 sec	STROBE	Click	Exit

Notes: The flashlight automatically memorizes the last selected lighting mode (excluding Strobe mode) and applies it next time when turned on. Battery indication is always on if the light is switched on.

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegra opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

INDEX: VLF-AT255RG



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP68

— Class of protection against dust and moisture.
The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter