

VIDEX[®]

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265

TECHNICAL CARD



Tactical LED Flashlight



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 3 YEARS

COLD WHITE



6500K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kúlm valge.

General parameters

Light source replaceable no

Type of light source

Dimmable no

Technology LED

Electrical parameters

On-mode power (Pon) 20 W

Input interface USB-C

Photometric parameters

Useful luminous flux of the light source (Φ_{use}) 2000 Lm

Correlated color temperature 6500K (cold white)

Peak luminous intensity 95600 cd

Additional information

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265

Housing colour	Black
Fall protection	3 m
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Heavy-anodized aircraft aluminum

Dimensions

EAN	4820246484237
Height	145 mm
Width	40 mm
Depth	31 mm
Outer box	20 pcs.
Unit nett weight	163g
In the package	1 pc.

Signs marking goods

Packaging marking CE, Utilization

VIDEX[®]

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265

VIDEX[®]

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265

VIDEX[®]

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.