

INDEX: VLF-AT265

TECHNICAL CARD



Tactical LED Flashlight





INDEX: VLF-AT265











IP6

Correlated color temperature	white)
Peak luminous intensity	95600 cd

WARRANTY 3 YEARS



Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / KaltweiB / Alb rece / Šalta balta / Auksti balta / Kűlm valge.

General parameters

Operation mode	TURBO, MIDDLE, MOON, STROBE
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	20 W
Input interface	USB-C

Photometric parameters

light source (Φ use)

Additional information

Housing colour	Black
Fall protection	3 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 21700, Li- ion 18650
Battery voltage	3.7 V
Battery capacity	4000 mAh
Battery indicator	5 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Heavy-anodized aircraft aluminum

Dimensions

EAN	4820246484237
Height	145 mm
Depth	31 mm
Width	40 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	163g



INDEX: VLF-AT265

Signs marking goods

Packaging marking

CE, Utilization











INDEX: VLF-AT265











INDEX: VLF-AT265







We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The protection is effective in case of a fall from a height of up to 3 meters



- The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.

The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter

Date: 2.07.2025