

TECHNICAL CARD



Universal Battery charger

VIDEX®



Free

WARRANTY 1 YEAR

General parameters

Compatible	AA, AAA
------------	---------

Electrical parameters

Input interface	Micro USB
-----------------	-----------

Electric shock protection class	II
---------------------------------	----

Additional information

Housing colour	Black
----------------	-------

Operating temperature range	0° +35°C
-----------------------------	----------

Battery voltage	1.2 V
-----------------	-------

Battery type	Ni-MH / Cd
--------------	------------

Mercury content	Does not contain
-----------------	------------------

Housing material	ABS
------------------	-----

Dimensions

EAN	4820246483162
-----	---------------

In the package	1 pc.
----------------	-------

Height	88 mm
--------	-------

Outer box	20 pcs.
-----------	---------

Width	72 mm
-------	-------

Depth	30 mm
-------	-------

VIDEX VCH-N401

INDEX: VCH-N401

Unit nett weight	60g
------------------	-----

Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------



INDEX: VCH-N401



VIDEX®

VIDEX VCH-N401

INDEX: VCH-N401

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The product does not contain mercury