

**INDEX: VCH-UT201** 

# **TECHNICAL CARD**



Universal Battery charger





**INDEX: VCH-UT201** 



## Signs marking goods

Packaging marking

CE, Utilization

### **WARRANTY 1 YEAR**

### **Electrical parameters**

Input interface	USB-C
Electric shock protection class	II

#### **Additional information**

Housing colour	Black
Operating temperature range	0° +35°C
Battery voltage	3.2 V, 3.7 V, 1.2 V
Battery type	LiFePO4, Li- ion / IMR, Ni- MH / Cd
Mercury content	Does not contain
Housing material	ABS

#### **Dimensions**

EAN	4820118296562
In the package	1 pc.
Height	135 mm
Outer box	20 pcs.
Width	73 mm
Depth	37 mm
Unit nett weight	132g







INDEX: VCH-UT201











**INDEX: VCH-UT201** 





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product does not contain mercury

Date: 18.11.2025