



INDEX: VL-AR082G

TECHNICAL CARD



Facade double-sided luminaire







VIDEX-2XE27-PORTER-GRAY

INDEX: VL-AR082G









Outer box	12 pcs.
Width	108 mm
Depth	165 mm

WARRANTY 2 YEARS

General	parameters
---------	------------

Light source replaceable	end user

Electrical parameters

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	1

Additional information

Place of installation	Wall
Place of application	outdoor
Impact protection	IK07
Housing colour	Gray
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP54
·	

Dimensions

EAN	4820246482363
Height	300 mm








VIDEX-2XE27-PORTER-GRAY

INDEX: VL-AR082G





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product must be used outdoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



- The product withstands a medium impact (e.g., from a blunt object)



- Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product is protected against the ingress of water and dust particles into the housing

Date: 18.11.2025