



**INDEX: VL-AR05-03082S** 

# **TECHNICAL CARD**



Garden luminaire





### VIDEX-3W-LUKAS-SILVER 80CM

### **INDEX: VL-AR05-03082S**
















Terminal block

Free









IP54

# WARRANTY 2 YEARS



Warm White / Ciepta biel / Tepla bila / Blanc chaud / Tepla biela / Warm wit / Meleg feher / Topla bela / Topla bijela / WarmweiB / Alb cald / Šiltai balta / Silti balta / Soe valge / Топло бяла / Bianco caldo.

### **General parameters**

Light source or containing product	Containing product
Control gear replaceable	no
Light source replaceable	no

### Type of light source

Dimmable	no
Technology	LED
Energy efficiency class of the contained light source	F

### **Electrical parameters**

On-mode power (Pon)	3 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	26 mA

### **Photometric parameters**

Useful luminous flux of the contained light source (Фuse)	300 Lm
Correlated color temperature	2700K (warm white)
Beam angle	360°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	50000 h
CRI Min	Ra 80
CRI Max	Ra 88

### **Additional information**

Place of installation	Floor
Place of application	outdoor
Impact protection	IK07
Housing colour	Silver
Ultraviolet radiation	no
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP54
Housing material	Stainless Steel

### **Dimensions**

**EAN** 4820246481083



# VIDEX-3W-LUKAS-SILVER 80CM

## **INDEX: VL-AR05-03082S**

In the package	1 pc.
Outer box	12 pcs.
Height	800 mm
Width	76 mm
Depth	76 mm

# Signs marking goods

### Packaging marking

Recycling of waste, CE, Utilization









# 76 MM WW 008

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

### VIDEX-3W-LUKAS-SILVER 80CM

### INDEX: VL-AR05-03082S



The product must be used outdoors



Waste recycling after the end of the product's service



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— Rated beam angle



— Ra > 80 - color rendering index



— Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product is protected against the ingress of water and dust particles into the housing

Date: 18.11.2025