

TECHNICAL CARD



Facade luminaire



VIDEX®



WARRANTY 3 YEARS

WARM WHITE



Warm White / Ciepła biel / Tepla bila / Blanc chaud / Tepla biela / Warm wit / Meleg feher / Topla bela / Topla bijela / Warmweiß / Alb cald / Šiltai balta / Silti balta / Soe valge / Тепло бяла / Bianco caldo.

General parameters

Control gear replaceable no

Light source replaceable no

Type of light source

Energy class of the light source F

Dimmable no

Electrical parameters

On-mode power (Pon) 3 W

Rated voltage, frequency AC 220-240 V, 50/60 Hz

Rated current 26 mA

Input interface Terminal block

Photometric parameters

VIDEX-3W-PELLE-BLACK

INDEX: VL-AR031-032B

Useful luminous flux of the light source (Φuse) 270 Lm

Correlated color temperature 2700K (warm white)

Beam angle 120°

Color rendering index (CRI) Ra > 80

Lifetime 50000 h

On/Off cycles 20000

Additional information

Place of installation Wall

Place of application outdoor

Housing colour Black

Ultraviolet radiation no

Operating temperature range -20° +40°C

Mercury content Does not contain

Ingress protection IP54

Housing material Aluminum

Dimensions



EAN 4820246480857

Height 81 mm

Width 68 mm

Depth 92 mm

Outer box 20 pcs.

VIDEX®**VIDEX-3W-PELLE-BLACK****INDEX: VL-AR031-032B**

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

Date: 30.12.2024