



**INDEX: VL-BHD02-09CBB** 

## **TECHNICAL CARD**



WALL-AND-CEILING-MOUNTED LED LIGHT FITTING

















#### VIDEX BHD02 9W 2400-3200-4300K BLACK

#### **INDEX: VL-BHD02-09CBB**

# -CRI-

Ra ≥ 90









Free











Free



#### **WARRANTY 3 YEARS**

#### **General parameters**

Light source or containing product	Containing product
Light source replaceable	no

#### Type of light source

Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	yes
Mains (MLS) or non-mains (NMLS) light source	MLS
High luminance light source	No
Anti-glare shield	No
Technology	LED
Energy efficiency class of the contained light source	E

#### **Electrical parameters**

On-mode power (Pon)	9 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	45 mA
Input interface	Terminal block
Electric shock protection class	II
Displacement factor (cos φ1)	0.9
Survival factor	1
Energy consumption in on-mode of the light source (kWh/1000h)	9

#### **Photometric parameters**

Useful luminous flux of the contained light source (Фuse)	1200 Lm
Correlated color temperature	2400K (warm white), 3200K (warm white), 4300K (neutral white)
Beam angle	160°
Color rendering index (CRI)	Ra > 90
On/Off cycles	25000
Lifetime (L70B50)	50000 h
Useful luminous flux of the light source reference	in a sphere (360°)
R9 colour rendering index value	>0
The lumen maintenance factor	≥96%
Flicker metric (Pst LM)	≤1



#### VIDEX BHD02 9W 2400-3200-4300K BLACK

#### **INDEX: VL-BHD02-09CBB**

Stroboscopic effect metric (SVM)	≤0.4	Width
Colour consistency in MacAdam ellipses (SDCM)	<6 (2400K), <6 (3200K), <6 (4300K)	Depth
CRI Min	Ra 90	Unit nett weight
CRI Max	Ra 95	Signs marking good

Width	130 mm
Depth	78 mm
Unit nett weight	450g

#### **Additional information**

Place of installation	Ceiling, Flat surface, Wall
Place of application	indoor, outdoor
Impact protection	IK08
Housing colour	Black
Diffuser material	Polycarbonate (PC)
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Motion sensor	no
Operating temperature range	-30° +50°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Iron alloy, ABS

### **Packaging marking**

Recycling of waste, CE, Utilization



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

#### **Dimensions**

EAN	4820246487795
In the package	1 pc.
Outer box	30 pcs.
Height	130 mm



#### VIDEX BHD02 9W 2400-3200-4300K BLACK

**INDEX: VL-BHD02-09CBB** 



The product must be used indoors



The product must be used outdoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



Minimum distance from the illuminated object



The product can be installed and used in/on normally flammable surfaces



Waste recycling after the end of the product's service



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Ra > 90 - color rendering index



Rated On/off cycles



The product withstands strong impacts (e.g., from a heavy object)



Nominal lifetime (hours)



The product does not emit ultraviolet light



The product is incompatible with light regulators



Operating temperatures range



The flickering of the light does not exceed the permissible level



The product has minimal flickering, which should not cause discomfort or danger



The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions

Date: 19.11.2025