

VIDEX VL-SPF24E-B

INDEX: VL-SPF24E-B

TECHNICAL CARD



Wall-mounted spot luminaire











VIDEX VL-SPF24E-B

INDEX: VL-SPF24E-B



















WARRANTY 2 YEARS

The decorative wall luminaire is intended for installation near sofas, armchairs and beds. With a mechanical switch, it's great for reading and for bedside lighting. The body of the lamp is made of aluminum - a light and durable metal that is not subject to corrosion. The surface of the case is covered with matte paint with a sandy texture, resistant to small scratches.

General parameters

Light source or containing product	Containing product
Light source replaceable	end user

Type of light source

Dimmable	no
Technology	LED
Energy efficiency class of the contained light source	G

Electrical parameters

On-mode power (Pon)	5 W (back light)

Energy consumption in on-mode of the light source (kWh/1000h)	5
Electric shock protection class	I
Input interface	Terminal block
Rated voltage, frequency	AC 220-240 V, 50/60 Hz, AC 185-240 V, 50/60 Hz (back light)

Photometric parameters

Useful luminous flux of the contained light source (Φ use)	380 Lm (backlight)
Correlated color temperature	2700K (back light)
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	40000 h
Useful luminous flux of the light source reference	in a sphere (360°)

Additional information

Place of installation	Wall
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum



VIDEX VL-SPF24E-B

INDEX: VL-SPF24E-B

Dimensions

EAN	4820246485845
In the package	1 pc.
Outer box	20 pcs.
Height	160 mm, 100 mm, 110 mm
Width	55 mm, 160 mm
Depth	55 mm, 31 mm
Unit nett weight	500g



Signs marking goods

Packaging marking

CE, Utilization









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

VIDEX VL-SPF24E-B

INDEX: VL-SPF24E-B



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Ra > 80 - color rendering index



— Rated On/off cycles



The product withstands a medium impact (e.g., from a blunt object)



— Nominal lifetime (hours)



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.

Protection against solid objects larger than 12 mm; no protection against moisture

Date: 18.11.2025