

VIDEX for GX53 lamp VL-SPF16A-B

**INDEX: VL-SPF16A-B** 

# **TECHNICAL CARD**



Ceiling spotlight luminaire

















### **WARRANTY 2 YEARS**

General	parameters
---------	------------

Light source replaceable end user

# **Electrical parameters**

Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Terminal block
Electric shock protection class	I

### **Additional information**

Place of installation	Ceiling, Recessed, Flat surface
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

### **Dimensions**

EAN	4820246484671
EAN	4820246484671

# VIDEX for GX53 lamp VL-SPF16A-B

### **INDEX: VL-SPF16A-B**

Height	50 mm
Depth	90 mm
Width	90 mm
In the package	1 pc.
Outer box	50 pcs.
Unit nett weight	220g

# Signs marking goods

**Packaging marking** CE, Utilization








**INDEX: VL-SPF16A-B** 









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



# VIDEX for GX53 lamp VL-SPF16A-B

**INDEX: VL-SPF16A-B** 



The product must be used indoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



Operating temperatures range



— The product does not contain mercury



Class of protection against dust and moisture.

Protection against solid objects larger than 12 mm; no protection against moisture

Date: 2.04.2025