

TECHNICAL CARD



LED Bulb



VIDEX®



120°



Ra ≥ 80



ON/OFF

20 000



20 000 h



Not Dimmable



-20° +40°C



Free



IP20

WARRANTY 2 YEARS

NEUTRAL WHITE



4000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

Type of light source

| | |
|---|---|
| Energy class of the light source | F |
|---|---|

| | |
|-----------------|----|
| Dimmable | no |
|-----------------|----|

Electrical parameters

| | |
|----------------------------|-----|
| On-mode power (Pon) | 7 W |
|----------------------------|-----|

| | |
|---------------------------------|------------------------|
| Rated voltage, frequency | AC 220-240 V, 50/60 Hz |
|---------------------------------|------------------------|

| | |
|----------------------|-------|
| Rated current | 60 mA |
|----------------------|-------|

Photometric parameters

| | |
|--|--------|
| Useful luminous flux of the contained light source (Φuse) | 600 Lm |
|--|--------|

| | |
|-------------------------------------|-----------------------|
| Correlated color temperature | 4000K (neutral white) |
|-------------------------------------|-----------------------|

| | |
|-------------------|------|
| Beam angle | 120° |
|-------------------|------|

VIDEX-GU10-7W-NW

INDEX: VLE-MR16e-07104


| | |
|---|--------------------|
| Color rendering index (CRI) | Ra > 80 |
| On/Off cycles | 20000 |
| Lifetime | 20000 h |
| Useful luminous flux of the light source reference | in a sphere (360°) |

Additional information

| | |
|------------------------------------|------------------|
| Place of application | indoor |
| Operating temperature range | -20° +40°C |
| Mercury content | Does not contain |
| Ingress protection | IP20 |

Dimensions

| | |
|------------------|---------------|
| EAN | 5904405540527 |
| Height | 55 mm |
| Depth | 50 mm |
| Width | 50 mm |
| Outer box | 20 pcs. |



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product must be used indoors



120°

Rated beam angle



Ra > 80

Ra > 80 - color rendering index



20 000

Rated On/off cycles



20 000 h

Nominal lifetime (hours)



Not Dimmable

The product is incompatible with light regulators



-20° +40°C

Operating temperatures range



Free

The product does not contain mercury



IP20

Class of protection against dust and moisture.
Protection against solid objects larger than 12 mm; no protection against moisture