

## TECHNICAL CARD




LED Downlight Fixture



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

## INDEX: VLE-DLBS-064



## WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutalus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

## General parameters

Light source or containing product	Containing product
Control gear replaceable	-
Light source replaceable	by the producer

## Type of light source

Dimmable	no
Energy efficiency class of the contained light source	F

## Electrical parameters

On-mode power (Pon)	6 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	45 mA

Input interface	Free wire ends
Electric shock protection class	II

## Photometric parameters

Correlated color temperature	4000K (neutral white)
Useful luminous flux of the contained light source (Φ <sub>use</sub> )	620 Lm
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)

## Additional information

Place of installation	Ceiling, Recessed
Place of application	indoor
Housing colour	White
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Plastic

## Dimensions


EAN	5904405540893
-----	---------------

**VIDEX®**

VIDEX-DOWNLIGHT-LED-DLBS-064-6W-NW


**INDEX: VLE-DLBS-064**

<b>Height</b>	120 mm
<b>Depth</b>	27 mm
<b>Width</b>	120 mm
<b>Outer box</b>	40 pcs.



**INDEX: VLE-DLBS-064**

30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



120°

— Rated beam angle



Ra ≥ 80

— Ra > 80 - color rendering index



ON/OFF  
20 000

— Rated On/off cycles



30 000 h

— Nominal lifetime (hours)



Free

— The product does not emit ultraviolet light



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP20

— Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture