

## TECHNICAL CARD



LED Headlamp

# VIDEX®



## WARRANTY 2 YEARS

### General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, RED HIGH, RED MIDDLE, RED LOW, RED FLASH
Light source replaceable	no

### Type of light source

Dimmable	yes
Technology	LED

### Electrical parameters

Input interface	USB-C
-----------------	-------

### Photometric parameters

Useful luminous flux of the contained light source (Φ <sub>use</sub> )	1000 Lm
Correlated color temperature	5000K (neutral white), Red
Peak luminous intensity	11660 cd

### Additional information

Housing colour	Black
----------------	-------

## VIDEX VLF-H047Z 1000Lm 5000K

### INDEX: VLF-H047Z

Fall protection	1 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery capacity	2000 mAh
Battery type	Li-pol
Battery indicator	5 level
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Polyamide

### Dimensions

EAN	4820246489560
In the package	1 pc.
Outer box	20 pcs.
Height	49 mm
Width	80 mm
Depth	46 mm
Unit nett weight	123g

### Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------

**VIDEX®**

VIDEX VLF-H047Z 1000Lm 5000K

**INDEX: VLF-H047Z**

**VIDEX®**

VIDEX VLF-H047Z 1000Lm 5000K

**INDEX: VLF-H047Z**

**VIDEX<sup>®</sup>**

VIDEX VLF-H047Z 1000Lm 5000K

**INDEX: VLF-H047Z**

**VIDEX<sup>®</sup>**

VIDEX VLF-H047Z 1000Lm 5000K

**INDEX: VLF-H047Z**

**VIDEX<sup>®</sup>**

VIDEX VLF-H047Z 1000Lm 5000K

**INDEX: VLF-H047Z**

# VIDEX®

## VIDEX VLF-H047Z 1000Lm 5000K

### INDEX: VLF-H047Z

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



— The product supports brightness adjustment



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions