

**VIDEX**<sup>®</sup>

VIDEX VLF-H085-OR 400Lm 5000K

**INDEX: VLF-H085-OR**

## TECHNICAL CARD



LED Headlamp



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®



## WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

### General parameters

<b>Operation mode</b>	HIGH, LOW, FLASH, COB + HIGH, COB HIGH, COB LOW, RED ON, RED FLASH
<b>Light source replaceable</b>	no

### Type of light source

<b>Dimmable</b>	no
<b>Technology</b>	LED

### Electrical parameters

<b>On-mode power (Pon)</b>	5 W + COB 5 W
<b>Input interface</b>	USB-C

### Photometric parameters

<b>Useful luminous flux of the contained light source (Φ<sub>use</sub>)</b>	400 Lm
---	--------

## VIDEX VLF-H085-OR 400Lm 5000K

### INDEX: VLF-H085-OR

<b>Peak luminous intensity</b>	3000 cd
<b>Correlated color temperature</b>	5000K (neutral white)

### Additional information

<b>Housing colour</b>	Orange
<b>Fall protection</b>	2 m
<b>Operating temperature range</b>	-20° +40°C
<b>Battery voltage</b>	3.7 V
<b>Battery type</b>	Li-pol
<b>Battery capacity</b>	850 mAh
<b>Battery indicator</b>	5 level
<b>Battery replaceable</b>	no
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP65
<b>Housing material</b>	Polyamide, Nylon

### Dimensions

<b>EAN</b>	4820246484251
<b>In the package</b>	1 pc.
<b>Height</b>	41 mm
<b>Outer box</b>	20 pcs.
<b>Width</b>	50 mm
<b>Depth</b>	34 mm
<b>Unit nett weight</b>	72g

INDEX: VLF-H085-OR

## Signs marking goods

Packaging marking

CE, Utilization



# VIDEX®

VIDEX VLF-H085-OR 400Lm 5000K

INDEX: VLF-H085-OR



**VIDEX<sup>®</sup>**

VIDEX VLF-H085-OR 400Lm 5000K

**INDEX: VLF-H085-OR**



# VIDEX®

VIDEX VLF-H085-OR 400Lm 5000K

INDEX: VLF-H085-OR



# VIDEX®

## VIDEX VLF-H085-OR 400Lm 5000K

### INDEX: VLF-H085-OR



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 2 meters



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions

Date: 24.06.2026