


TECHNICAL CARD



LED Linkable Linear Light IP65




Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®

VIDEX BNWL05 50W 1.5M 5000K 8000Lm Black

INDEX: VL-BNWL05-50155B



WARRANTY 5 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source or containing product	Light source
Light source replaceable	no
Control gear replaceable	-

Type of light source

Energy class of the light source	C
Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light source	MLS

High luminance light source	No
Anti-glare shield	No
Technology	LED

Electrical parameters

On-mode power (Pon)	50 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	241 mA
Input interface	Terminal block
Electric shock protection class	I
Displacement factor (cos φ1)	0.9
Survival factor	0.9
Energy consumption in on-mode of the light source (kWh/1000h)	50

Photometric parameters

Useful luminous flux (Φuse)	8000 Lm
Correlated color temperature	5000K (neutral white)
Beam angle	140°
Color rendering index (CRI)	Ra > 80
On/Off cycles	25000
Lifetime (L70B50)	50000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.35
Chromaticity coordinates (y)	0.36
R9 colour rendering index value	>0

INDEX: VL-BNWL05-50155B

The lumen maintenance factor	≥96.5%
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4
Colour consistency in MacAdam ellipses (SDCM)	<6 (5000K)
CRI Min	Ra 80
CRI Max	Ra 88

Additional information

Place of installation	Ceiling, Flat surface, Wall, Suspension
Place of application	indoor, outdoor
Impact protection	IK08
Housing colour	Black
Minimum distance from the illuminated object	0.5 m
Ultraviolet radiation	no
Operating temperature range	-25° +40°C
Suitable for installation in normally flammable surfaces	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	PC

Dimensions


EAN	4820246488426
In the package	1 pc.

Outer box	9 pcs.
Height	71 mm
Width	1490 mm
Depth	61 mm
Unit nett weight	1.5kg

Signs marking goods

Packaging marking

Recycling of waste, CE, Utilization



VIDEX®

VIDEX BNWL05 50W 1.5M 5000K 8000Lm Black

INDEX: VL-BNWL05-50155B

VIDEX[®]

VIDEX BNWL05 50W 1.5M 5000K 8000Lm Black

INDEX: VL-BNWL05-50155B

VIDEX[®]

VIDEX BNWL05 50W 1.5M 5000K 8000Lm Black


INDEX: VL-BNWL05-50155B

VIDEX®

VIDEX BNWL05 50W 1.5M 5000K 8000Lm Black

INDEX: VL-BNWL05-50155B

30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,



The product must be used indoors



The product must be used outdoors



Protection against electric shock class I. A product in which the means of protection against electric shock, in addition to the main insulation, is an additional protective circuit connected to the grounding of the power supply network



Minimum distance from the illuminated object



The product can be installed and used in/on normally flammable surfaces



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— Ra > 80 - color rendering index



— Rated On/off cycles



— The product withstands strong impacts (e.g., from a heavy object)



— Nominal lifetime (hours)



— The product does not emit ultraviolet light



— The product is incompatible with light regulators



— The flickering of the light does not exceed the permissible level



— The product has minimal flickering, which should not cause discomfort or danger



— Colour consistency in MacAdam ellipses (SDCM)



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions