

VIDEX-E27-R80-9W-FITO

INDEX: VLE-R80FF-09271

TECHNICAL CARD



LED Plant Grow Bulb













120°









-20° +40°C







VIDEX-E27-R80-9W-FITO

INDEX: VLE-R80FF-09271

Rated current	78 mA
Displacement factor (cos φ1)	-
Survival factor	-

Photometric parameters

•	
Correlated color temperature	1200K (bicolor)
Beam angle	120°
Color rendering index (CRI)	Ra > 40
On/Off cycles	20000
Lifetime (L70B50)	20000 h
Useful luminous flux of the light source reference	in a wide cone (120°)
Chromaticity coordinates (x)	-
Chromaticity coordinates (y)	-
R9 colour rendering index value	-
The lumen maintenance factor	-
Flicker metric (Pst LM)	-
Stroboscopic effect metric (SVM)	-
Colour consistency in MacAdam ellipses (SDCM)	<6 (1200K)

Additional information

Place of application	indoor
Operating temperature range	-20° +40°C
Mercury content	Does not contain

WARRANTY 2 YEARS



General parameters

Light source or containing product	Light source
3.	5

Type of light source

Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	-
Connected light source (cls)	-
Color-tunable light source	-
Mains (MLS) or non-mains (NMLS) light source	-
High luminance light source	-
Anti-glare shield	-
Technology	LED

Electrical parameters

On-mode power (Pon)	9 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz



VIDEX-E27-R80-9W-FITO

INDEX: VLE-R80FF-09271

Dimensions

EAN	5904405542415
In the package	1 pc.
Outer box	20 pcs.
Height	115 mm
Width	80 mm
Depth	80 mm
Unit nett weight	45g




Signs marking goods

Packaging marking

Recycling of waste, CE, Not suitable for use under moisture, Utilization





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



VIDEX-E27-R80-9W-FITO

4/4

INDEX: VLE-R80FF-09271



The product must be used indoors



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



Not suitable for use under moisture



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



— Ra > 40 - color rendering index



— Rated On/off cycles



Nominal lifetime (hours)



- The product is incompatible with light regulators





Operating temperatures range



Colour consistency in MacAdam ellipses (SDCM)



The product does not contain mercury



Class of protection against dust and moisture.

Protection against solid objects larger than 12 mm; no protection against moisture

Date: 26.11.2025