

TECHNICAL CARD



LED Portable Flashlight

VIDEX®



WARRANTY 3 YEARS

NEUTRAL WHITE



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, MOON, RED HIGH, RED LOW, RED FLASH
Light source replaceable	no
Battery Warranty	1 year

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

Photometric parameters

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R

Useful luminous flux of the contained light source (Φuse)	1000 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	5250 cd

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery voltage	3.7 V
Battery capacity	2200 mAh
Battery type	Li-ion 18650
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Anodized aluminum

Dimensions

EAN	4820246486774
In the package	1 pc.
Outer box	20 pcs.
Height	118 mm
Width	25 mm
Depth	25 mm
Unit nett weight	78g

VIDEX®

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R

Signs marking goods

Packaging marking

CE, Utilization



VIDEX®

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R



VIDEX[®]

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R

VIDEX[®]

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R

VIDEX®

VIDEX VLF-A232R 1000Lm 5000K

INDEX: VLF-A232R



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



Not Dimmable

— The product is incompatible with light regulators



-20° - +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP66

— Class of protection against dust and moisture. The product has full protection against dust and powerful water jets