

INDEX: VL-NL053W-S

TECHNICAL CARD



LED RECHARGEABLE NIGHT LIGHT with MOTION **SENSOR**













INDEX: VL-NL053W-S











| CRI Min | Ra 80 |
|---------|-------|
| CRI Max | Ra 88 |





WARRANTY 2 YEARS

General parameters

Type of light source

| Dimmable | yes |
|------------|-----|
| Technology | LED |

Electrical parameters

| On-mode power (Pon) | 0.8 W |
|---------------------------------|-------|
| Input interface | USB-C |
| Electric shock protection class | III |

Photometric parameters

| Luminous flux | 50 Lm |
|------------------------------|---|
| Correlated color temperature | 6500K (cold white), 4500K (neutral white), 3000K (warm white) |
| Beam angle | 120° |
| Color rendering index (CRI) | Ra > 80 |
| | |

Additional information

| Place of application | indoor |
|-----------------------------|------------------|
| Housing colour | White |
| Ultraviolet radiation | no |
| Motion sensor | yes |
| Sensor type | PIR |
| Sensor time delay | 20 s |
| Sensor detection angle | 120° |
| Sensor detection distance | ≤6 m |
| Operating temperature range | -20° +40°C |
| Battery type | Li-pol |
| Battery voltage | 3.7 V |
| Battery capacity | 1100 mAh |
| Battery replaceable | no |
| Mercury content | Does not contain |
| Ingress protection | IP20 |
| Housing material | ABS |

Dimensions

| EAN | 4820246486460 |
|----------------|---------------|
| Height | 110 mm |
| Depth | 19 mm |
| Width | 45 mm |
| In the package | 1 pc. |



INDEX: VL-NL053W-S

Outer box 24 pcs.
Unit nett weight 77g

Signs marking goods

Packaging marking

Recycling of waste, CE, Utilization











INDEX: VL-NL053W-S








INDEX: VL-NL053W-S









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



6/6

INDEX: VL-NL053W-S



The product must be used indoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— Rated beam angle



— Ra > 80 - color rendering index



— The product does not emit ultraviolet light



The product supports brightness adjustment



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture.
 Protection against solid objects larger than 12 mm; no protection against moisture

Date: 10.04.2025