

## TECHNICAL CARD



LED Solar Park Light with motion sensor



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

## INDEX: VL-GLSO-1254-S



## WARRANTY 2 YEARS

### General parameters

Light source replaceable no

### Type of light source

Technology LED

### Electrical parameters

Rated voltage, frequency 3.2 V

Electric shock protection class III

### Photometric parameters

Correlated color temperature 5000K (neutral white), 3000K (warm white)

Beam angle 360°, 60°

Color rendering index (CRI) Ra > 80

On/Off cycles 20000

Lifetime (L70B50) 30000 h

Rated number of the battery charge cycles 2000 cycles

Colour consistency in MacAdam ellipses (SDCM) <6 (5000K)

### Additional information

Battery power	38.4 Wh
Place of installation	Pillar
Place of application	outdoor
Impact protection	IK06
Housing colour	Black
Diffuser material	ABS
Minimum distance from the illuminated object	0.5 m
Motion sensor	yes
Operating temperature range	-10° +40°C
Battery voltage	3.2 V
Battery capacity	12000 mAh
Battery type	LiFePO4
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP54
Housing material	ABS

### Dimensions

EAN	4820246484329
In the package	1 pc.
Outer box	5 pcs.
Height	100 mm
Width	430 mm

# VIDEX®

## VIDEX VL-GLSO-1254-S

### INDEX: VL-GLSO-1254-S

**Depth** 430 mm

**Unit nett weight** 2.51kg

### Signs marking goods


### Packaging marking

Recycling of  
waste, CE,  
Utilization




**VIDEX<sup>®</sup>**

VIDEX VL-GLSO-1254-S

**INDEX: VL-GLSO-1254-S**

## INDEX: VL-GLSO-1254-S



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product must be used outdoors



Class III protection against electric shock - ensured by supplying a specific product with a safe very low voltage (SELV) without the risk of creating a voltage above safe levels



Minimum distance from the illuminated object



Waste recycling after the end of the product's service life



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



Rated beam angle



Ra > 80 - color rendering index



Rated On/off cycles



Nominal lifetime (hours)



Operating temperatures range



Rated number of the battery charge cycles



Colour consistency in MacAdam ellipses (SDCM)



The product does not contain mercury



Class of protection against dust and moisture. The product is protected against the ingress of water and dust particles into the housing