

VIDEX®

VIDEX-E14-C35-6W-FIL-NW

INDEX: VLE-C35F-06144

TECHNICAL CARD




LED Bulb



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

VIDEX®



WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

General parameters

Light source or containing product Light source

Type of light source

Energy class of the light source	E
Dimmable	no
Directional (DLS) or non-directional (NDLS) light source	NDLS
Connected light source (cls)	no
Color-tunable light source	no
Mains (MLS) or non-mains (NMLS) light source	MLS
High luminance light source	No
Anti-glare shield	No

VIDEX-E14-C35-6W-FIL-NW

INDEX: VLE-C35F-06144

Technology	LED
Electrical parameters	
On-mode power (Pon)	6 W
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Rated current	52 mA
Displacement factor (cos φ1)	0.5
Survival factor	0.9
Energy consumption in on-mode of the light source (kWh/1000h)	6
Photometric parameters	
Useful luminous flux (Φuse)	806 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	360°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime (L70B50)	20000 h
Useful luminous flux of the light source reference	in a sphere (360°)
Chromaticity coordinates (x)	0.38
Chromaticity coordinates (y)	0.38
R9 colour rendering index value	>0
The lumen maintenance factor	≥94.8%
Flicker metric (Pst LM)	≤1
Stroboscopic effect metric (SVM)	≤0.4
Colour consistency in MacAdam ellipses (SDCM)	<6 (4000K)

VIDEX®

VIDEX-E14-C35-6W-FIL-NW

INDEX: VLE-C35F-06144

CRI Min	Ra 80
----------------	-------

CRI Max	Ra 88
----------------	-------

Additional information

Place of application	indoor
-----------------------------	--------

Operating temperature range	-20° +40°C
------------------------------------	------------

Mercury content	Does not contain
------------------------	------------------

Ingress protection	IP20
---------------------------	------

Dimensions

EAN	5904405540114
------------	---------------

In the package	1 pc.
-----------------------	-------

Outer box	20 pcs.
------------------	---------

Height	98 mm
---------------	-------

Width	35 mm
--------------	-------

Depth	35 mm
--------------	-------

Unit nett weight	14g
-------------------------	-----

Signs marking goods

Packaging marking


Recycling of waste, CE, Not suitable for use under moisture, Utilization



VIDEX®

VIDEX-E14-C35-6W-FIL-NW

INDEX: VLE-C35F-06144



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

-  The product must be used indoors
-  Waste recycling after the end of the product's service life
-  The product meets the requirements of EU directives
-  Not suitable for use under moisture
-  It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste
-  — Rated beam angle
360°
-  — Ra > 80 – color rendering index
Ra = 80
-  — Rated On/off cycles
ON/OFF
20 000
-  — Nominal lifetime (hours)
20 000 h
-  — The product is incompatible with light regulators
Not Dimmable
-  — Operating temperatures range
-20° +40°C
-  — The flickering of the light does not exceed the permissible level
No Flicker
-  — The product has minimal flickering, which should not cause discomfort or danger
No Flicker
-  — Colour consistency in MacAdam ellipses (SDCM)
+5 SDCM
CCT 4000K
-  — The product does not contain mercury
Hg Free
-  — Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture
IP20