

## TECHNICAL CARD




LED Frameless Downlight Fixture



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.

# VIDEX®



## WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálina biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrálno bijela / Neutralweiß / Alb neutru / Neutrus balta / Neitrāls balta / Neutraalne valge / Нейтрално бяла / Bianco neutro.

## General parameters

Light source or containing product	Containing product
Control gear replaceable	by the producer
Light source replaceable	by the producer

## Type of light source

Dimmable	no
Energy efficiency class of the contained light source	E

## Electrical parameters

Rated voltage, frequency	AC 85-265 V, 50/60 Hz
Rated current	130 mA

## VIDEX-DOWNLIGHT-LED-DLFR-15W-NW

### INDEX: VLE-DLFR-154

Input interface	Free wire ends
Electric shock protection class	II

## Photometric parameters

Useful luminous flux of the contained light source ( $\Phi_{use}$ )	1950 Lm
Correlated color temperature	4000K (neutral white)
Beam angle	120°
Color rendering index (CRI)	Ra > 80
On/Off cycles	20000
Lifetime	30000 h
Useful luminous flux of the light source reference	in a sphere (360°)

## Additional information

Place of installation	Ceiling, Recessed
Place of application	indoor
Housing colour	White
Diffuser material	Plastic
Ultraviolet radiation	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP54 / IP20
Housing material	Iron alloy



## Dimensions

# VIDEX®

## VIDEX-DOWNLIGHT-LED-DLFR-15W-NW

### INDEX: VLE-DLFR-154

<b>EAN</b>	5904405540794
<b>Height</b>	120 mm
<b>Depth</b>	20 mm
<b>Width</b>	120 mm
<b>Outer box</b>	20 pcs.



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.

## INDEX: VLE-DLFR-154



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



— Rated beam angle



— Ra > 80 - color rendering index



— Rated On/off cycles



— Nominal lifetime (hours)



— The product does not emit ultraviolet light



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— IP54 - external part, IP20 - mounting part