

Артикул товару: VLF-H025C

ТЕХНІЧНА КАРТА



Налобний світлодіодний ліхтарик



Відповідно до положень Закону про WEEE забороняється викидати обладнання, позначене символом перекресленого контейнера, разом з іншим сміттям. Користувач, який бажає позбутися електронного та електричного обладнання, зобов'язаний повернути його в пункт прийому відпрацьованого обладнання. У складі обладнання відсутні небезпечні компоненти, які особливо негативно впливають на навколишнє середовище та здоров'я людини.

VIDEX®



ГАРАНТІЯ 2 РОКИ



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutrallyno bijela / Neutralweiß / Alb neutru / Neutrusus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

Загальні параметри

Режим роботи	HIGH, LOW, STROBE, COB, COB + HIGH, RED ON, RED FLASH
Замінюване джерело світла	ні

Тип джерела світла

З можливістю затемнення	ні
Технологія	LED

Електричні параметри

Потужність	5 Вт + COB
Інтерфейс підключення	USB-C

Фотометричні параметри

Корисний світловий потік вбудованого джерела світла (Φuse)	310 Лм
--	--------

VIDEX VLF-H025C 310Lm 5000K

Артикул товару: VLF-H025C

Пікова інтенсивність світла	1380 кд
Колірна температура світла	5000K (нейтральний білий)

Додаткова інформація

Колір корпусу	Чорний
Захист від падіння	1 м
Робоча температура	-20° +40°C
Напруга	3.7 В
Тип акумулятора	Li-ion
Ємність акумулятора	1800 мАг
Індикатор заряду батареї	5 level
Змінна батарея	ні
Вміст ртуті	не містить
Клас захисту, IP	IP65
Матеріал корпусу	Полікарбонат (PC)

Розміри

Штрих-код	4820246481076
В упаковці	1 шт.
Висота	46 мм
Кількість у коробі	20 шт.
Ширина	70 мм
Глибина	38 мм
Вага нетто одиниці	99г

Знаки маркування товарів

VIDEX®

VIDEX VLF-H025C 310Lm 5000K

Артикул товару: VLF-H025C

Маркування пакування

CE,
Утилізація

VIDEX[®]

VIDEX VLF-H025C 310Lm 5000K

Артикул товару: VLF-H025C



VIDEX®

VIDEX VLF-H025C 310Lm 5000K

Артикул товару: VLF-H025C



VIDEX®
MODEL | H025C

RECHARGEABLE LED
HEADLAMP WITH SENSOR



310
MAX LUMENS



VIDEX®
MODEL | H025C



MAIN LED CREE XTE
5W
5000K (Neutral white)

LOW BEAM LED COB
5W
5000K (Neutral white)

MAIN LED. 80° Beam angle and 74m max illumination distance.
LOW BEAM LED. 120° Beam angle and 7m max illumination distance.

Both light sources can work together reaching max brightness 310 lumens.

VIDEX®

VIDEX VLF-H025C 310Lm 5000K


Артикул товару: VLF-H025C



VIDEX®

VIDEX VLF-H025C 310Lm 5000K

Артикул товару: VLF-H025C



VIDEX®

VIDEX VLF-H025C 310Lm 5000K

Артикул товара: VLF-H025C

VIDEX®

MODEL | H025C

USB-C PORT



FULL CHARGE FOR AROUND 3.5 HOURS
THE CHARGING PORT COVERED BY THICK SILICONE, WHICH PREVENTS DUST AND WATER PENETRATE INSIDE THE DEVICE.

VIDEX®

MODEL | H025C

1800mAh. 600 CYCLES.



Built-in Li-polymer rechargeable can run for around 10 hours at one cycle and can replace thousands of primary batteries during its service life. An intelligent charge control circuit protects the battery from overdischarge and overcharge.

VIDEX®

MODEL | H025C

NYLON HEADBAND



THE HEADBAND IS MADE OF NYLON, WHICH IS AN ELASTIC AND WEAR-RESISTANT MATERIAL.

VIDEX®

MODEL | H025C

TILT MECHANISM



ADJUST THE HEADLAMP TILT ANGLE WITHIN 60 DEGREES.

VIDEX®

VIDEX VLF-H025C 310Lm 5000K

Артикул товару: VLF-H025C



VIDEX®
MODEL | H025C

1. Maximum power mode 250 Lm
2. Minimum power mode 95 Lm
3. COB mode (low beam) 75 Lm
4. COB+Maximum power 310 Lm
5. Flash mode
6. Red light
7. Red flashing light



VIDEX®
MODEL | H025C

LIGHTING MODES

LIGHTING MODES	HIGH	LOW	COB	COB+HIGH	FLASH
OUTPUT	250 Lm	95 Lm	75 Lm	310 Lm	95 Lm
RUNTIME	4h 50min	9h	10h 20min	3h	21h
DISTANCE	74m	46m	7m	74m	46m
INTENSITY	1380cd	520cd	12cd	1380cd	520cd
		RED ON	1.2 Lm / 8h	RED FLASH	1.2 Lm / 16h



VIDEX®
MODEL | H025C

PROGRAM ROOT

Start position	Action A	Result	Action B	Result
OFF	Press	ON SENSOR**	Hand wave	OFF/ ON
HIGH / LOW / FLASH / RED ON / RED FLASH / COB	Press	SENSOR*	Hand wave	OFF/ ON
ON / OFF	Press and hold for 0.5 sec	Battery status		
OFF	Press and hold for 3 sec	Lock	Press and hold for 3 sec	Unlock
OFF	Press	> ON HIGH > LOW > FLASH > RED ON > RED FLASH > OFF		
ON / OFF	Press and hold for 0.5 sec	COB ON	Press and hold for 0.5 sec	COB OFF

* Sensor remembers current lighting mode and applies it until the sensor mode will be deactivated.
Notes: The modes selection performs within 5 seconds. After this time, the next short press will turn off the light.
The headlamp automatically memorizes the last selected lighting mode (except COB mode) and applies it next time when turned on.
The Main Light modes and Flood Light (COB) mode can be turned on together unless the sensor is activated.



VIDEX®
MODEL | H025C

KIT CONTENT



USER'S MANUAL



HEADLAMP



HEADBAND



CHARGING CABLE USB-C

SIZES 70x46x38mm
WEIGHT: 99g (INCLUDING HEADBAND)

Ми залишаємо за собою право вносити технічні зміни. Дані, що містяться в цьому матеріалі не має юридичної сили.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślna 11, 30-732 Краків, Польща.



Продукт відповідає вимогам директив ЄС



Забороняється викидати сміттєве обладнання, позначене символом перекресленого контейнера, разом з іншим сміттям



— Захист ефективний при падінні з висоти до 1 метра



— Продукт несумісний із регуляторами світла



— Діапазон робочих температур



— Виріб не містить ртуті



— Клас захисту від пилу і вологі. Виріб має повний захист від пилу і від струменів води з усіх напрямків

Дата: 24.06.2026