

INDEX: VLF-A298

TECHNICAL CARD



LED Portable Flashlight





VIDEX VLF-A298 1500Lm 5000K

INDEX: VLF-A298

1m SHOCK RESISTANT









WARRANTY 3 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutra

General parameters

Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	10 W
Input interface	USB-C

Photometric parameters

Useful luminous flux of the contained light source (Фиѕе)	1500 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	11960 cd

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 18650, Li-ion 16340, Li-ion 18350
Battery voltage	3.7 V
Battery capacity	2200 mAh, 1100 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP66
Housing material	Anodized aluminum

Dimensions

EAN	4820246486781
Height	121 mm, 91 mm
Depth	30 mm
Width	30 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	90g

Signs marking goods

Packaging marking	CE, Utilization
3 3	•















VIDEX VLF-A298 1500Lm 5000K

INDEX: VLF-A298











VIDEX VLF-A298 1500Lm 5000K

INDEX: VLF-A298









We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste $\,$



The protection is effective in case of a fall from a height of up to 1 meter



- The product is incompatible with light regulators



Operating temperatures range



- The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and powerful water jets

Date: 29.03.2025