

INDEX: VL-SPF09R-B

TECHNICAL CARD



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.



Recessed spotlight luminaire VL-SPF09R-B

85 mm

INDEX: VL-SPF09R-B

Depth

×X	°c∭≣	₩g
~		
IK07	-25° +50°C	Free



WARRANTY 2 YEARS



Width	85 mm
Outer box	50 pcs.

General parameters

Light source replaceable	end user
Electrical parameters	
Rated voltage, frequency	AC 220-240 V, 50/60 Hz
Input interface	Free wire ends



Additional information

Place of installation	Ceiling, Recessed
Place of application	indoor
Impact protection	IK07
Housing colour	Black
Operating temperature range	-25° +50°C
Mercury content	Does not contain
Ingress protection	IP20
Housing material	Aluminum

Dimensions

EAN	4820246482899
Height	46 mm






Recessed spotlight luminaire VL-SPF09R-B

INDEX: VL-SPF09R-B





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

\bigcirc	Th	e product must be used indoors
К07	_	The product withstands a medium impact (e.g., from a blunt object)
"C -25" +50"C	_	Operating temperatures range
Free	_	The product does not contain mercury
IP20	_	Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture