

## TECHNICAL CARD



Tactical LED Flashlight

# VIDEX®



## WARRANTY 3 YEARS

### COLD WHITE



### 6500K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kúlm valge.

## General parameters

**Light source replaceable** no

## Type of light source

**Dimmable** no

**Technology** LED

## Electrical parameters

**On-mode power (Pon)** 20 W

**Input interface** USB-C

## Photometric parameters

**Useful luminous flux of the contained light source (Φ<sub>use</sub>)** 2000 Lm

**Correlated color temperature** 6500K (cold white)

**Peak luminous intensity** 95600 cd

## Additional information

## VIDEX VLF-AT265 2000Lm 6500K

### INDEX: VLF-AT265

<b>Housing colour</b>	Black
<b>Fall protection</b>	3 m
<b>Operating temperature range</b>	-20° +40°C
<b>Battery type</b>	Li-ion 21700, Li-ion 18650
<b>Battery voltage</b>	3.7 V
<b>Battery capacity</b>	4000 mAh
<b>Battery indicator</b>	5 level
<b>Battery replaceable</b>	yes
<b>Mercury content</b>	Does not contain
<b>Ingress protection</b>	IP68
<b>Housing material</b>	Heavy-anodized aircraft aluminum

## Dimensions

<b>EAN</b>	4820246484237
<b>Height</b>	145 mm
<b>Depth</b>	31 mm
<b>Width</b>	40 mm
<b>In the package</b>	1 pc.
<b>Outer box</b>	20 pcs.
<b>Unit nett weight</b>	163g

## Signs marking goods

**Packaging marking** CE, Utilization

**VIDEX®**

VIDEX VLF-AT265 2000Lm 6500K

**INDEX: VLF-AT265**

**VIDEX®**

VIDEX VLF-AT265 2000Lm 6500K

**INDEX: VLF-AT265**

# VIDEX®

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,  
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 3 meters



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP68

— Class of protection against dust and moisture. The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter

Date: 29.03.2025