

TECHNICAL CARD



Tactical LED Flashlight

VIDEX®



WARRANTY 3 YEARS

COLD WHITE



6500K

Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kúlm valge.

General parameters

| | |
|--------------------------|--------------------------------------|
| Operation mode | TURBO, MIDDLE, MOON, STROBE |
| Light source replaceable | no |
| Battery Warranty | 1 year |

Type of light source

| | |
|------------|-----|
| Dimmable | no |
| Technology | LED |

Electrical parameters

| | |
|---------------------|-------|
| On-mode power (Pon) | 20 W |
| Input interface | USB-C |

Photometric parameters

| | |
|--|----------|
| Useful luminous flux of the contained light source (Φ _{use}) | 2000 Lm |
| Peak luminous intensity | 95600 cd |

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265

Correlated color temperature 6500K (cold white)

Additional information

| | |
|-----------------------------|----------------------------------|
| Housing colour | Black |
| Fall protection | 3 m |
| Operating temperature range | -20° +40°C |
| Battery voltage | 3.7 V |
| Battery type | Li-ion 21700, Li-ion 18650 |
| Battery capacity | 4000 mAh |
| Battery indicator | 5 level |
| Battery replaceable | yes |
| Mercury content | Does not contain |
| Ingress protection | IP68 |
| Housing material | Heavy-anodized aircraft aluminum |

Dimensions

| | |
|------------------|---------------|
| EAN | 4820246484237 |
| In the package | 1 pc. |
| Height | 145 mm |
| Outer box | 20 pcs. |
| Width | 40 mm |
| Depth | 31 mm |
| Unit nett weight | 163g |

Signs marking goods

Packaging marking CE, Utilization

VIDEX[®]

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265

VIDEX[®]

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265

VIDEX®

VIDEX VLF-AT265 2000Lm 6500K

INDEX: VLF-AT265



We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



3m
SHOCK
RESISTANT

— The protection is effective in case of a fall from a height of up to 3 meters



Not Dimmable

— The product is incompatible with light regulators



-20° +40°C

— Operating temperatures range



Free

— The product does not contain mercury



IP68

— Class of protection against dust and moisture. The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter