

TECHNICAL CARD



Universal Battery charger

VIDEX®



Free

WARRANTY 1 YEAR

General parameters

Compatible	26650, 26500, 21700, 18650, 17500, 16340, 14500, 10440
------------	---

Electrical parameters

Input interface	Micro USB
Electric shock protection class	II

Additional information

Housing colour	Black
Operating temperature range	0° +35°C
Battery voltage	3.7 V
Battery type	Li-ion / IMR
Mercury content	Does not contain
Housing material	ABS

Dimensions

EAN	4820246483131
In the package	1 pc.
Height	100 mm
Outer box	20 pcs.

VIDEX VCH-L201

INDEX: VCH-L201

Width	60 mm
Depth	28 mm
Unit nett weight	55g

Signs marking goods

Packaging marking CE, Utilization



VIDEX®

VIDEX VCH-L201

INDEX: VCH-L201



VIDEX®

VIDEX VCH-L201

INDEX: VCH-L201

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The product does not contain mercury